



BF155 FST

The Blacklion BF155 FST regional steer features a broad 5 rib tread pattern to provide precise handling and excellent stability. Wide circumferential grooves efficiently evacuate water from the tread area. The BF155 FST is ideally suited for regional applications, pick-up & delivery and limited highway service. ST sizes featuring all steel construction are specifically designed for use in specialty trailer applications.

APPLICATIONS

- Regional Trucks
- Dump Trucks
- Refuse Trucks
- Pick-up & Delivery Trucks
- Intrastate & Local Buses

TIRE FEATURES

- SmartWay verified tires can improve fuel efficiency by 3 percent or more.
- Broad 5 rib design delivers precise handling.
- Wide circumferential grooves deliver exceptional wet traction.



SMARTWAY VERIFIED TIRE

Size	Ply	T.D.		Load Index		S.R.	O.D.	S.W.	R.W.	Load Carrying Capacity		A.P.
		32nds	Single	Dual	Single, lbs.					Dual, lbs.	psi	
ST235/80R16**	14	10	129	125	L	30.8	9.3	6.5	4,080	3,640	110	
ST235/85R16**	14	12	132	127	L	31.7	9.3	6.5	4,400	3,860	110	
11R22.5	14	18	144	142	L	41.5	11.0	8.25	6,175	5,840	105	
11R22.5	16	18	146	143	L	41.5	11.0	8.25	6,610	6,005	120	
*12R22.5	16	18	150	147	L	42.7	11.8	9.00	7,390	6,780	120	
295/75R22.5	14	18	144	141	L	39.9	11.7	8.25	6,175	5,675	110	
*315/80R22.5	18	18	154	151	L	42.4	12.3	9.00	8,270	7,610	120	
*315/80R22.5	20	18	156	153	L	42.4	12.3	9.00	8,820	8,045	125	
11R24.5	14	18	146	143	L	43.5	11.0	8.25	6,610	6,005	105	
11R24.5	16	18	149	146	L	43.5	11.0	8.25	7,160	6,610	120	
285/75R24.5	14	18	144	141	L	41.3	11.1	8.25	6,175	5,675	110	

**This tire size is not SmartWay® Verified ** All steel construction specifically designed for Trailer application only. Requires special high load capacity wheel. Consult wheel manufacturer for proper application. Tread may differ from image shown.